
YIILIGHTING



*These instructions are provided for your safety. It is very important that they are read completely before beginning the installation of your fixture.

*WE STRONGLY RECOMMEND INSTALLATION BY A LICENSED ELECTRICIAN.

Assembly Instructions

- *Shut off the main electrical supply from the main fuse box/circuit breaker.
- *Remove all parts from carton, and remove all packing material. Do not throw away any parts.
- 1. Thread all the wires of lampholders (X9) through the branching arms (X3) and thread into the central box.
- 2. Twist all the <u>blue wires</u> coming out from the arms with <u>blue wire</u> from the main wire together, and do the same to the brown wires. Then put the wires back to the central box and screw the poles to the central box.
- 3. Mark the position of the mounting plate's holes on your ceiling. Drill the ceiling holes for the plastic anchors. Install the provided plastic anchors into the holes you've just drilled. Mount the plate with the screws provided.
- 4. Thread the main wire from the pole through canopy and make electrical connections. Connect the <u>neutral wire(blue/white)</u> from main wire to the neutral wire from power supply and connect the <u>hot wire(brown/black)</u> from main wire to the hot wire from power supply.
- 5. Mount the fixture ceiling canopy to the mounting plate by sliding the fixture cover over the mounting plate and lock into place with the screws provided.
- 6. Put G9 bulbs on the lampholders and screw the glass shades and mini poles into place.
- 7. Reconnect electrical supply at fuse box/circuit breaker and test fixture.
- P.S. Blue/white is N wire; brown/black is L wire.

