



List of Parts

Mounting Plate	Tapping screws	Canopy
Canopy Screws	Canopy ball nuts	Metal rods
Nuts	Acrylic rings	

Safety Instructions

*These instructions are provided for your safety. It is very important that they are read completely before beginning the installation of your fixture.

*WE STRONGLY RECOMMEND INSTALLATION BY A LICENSED ELECTRICIAN.

Assembly Instructions

*Shut off the main electrical supply from the main fuse box/circuit breaker.

*Remove all parts from carton, and remove all packing material. Do not throw away any parts.

- Carefully pull the wiring from the outlet box. Thread the wires through the mounting plate. Affix mounting plate to ceiling outlet box with tapping screws provided. (If you are going to mount fixture in a concrete ceiling, please replace the tapping screws with expansion screws) #①②
- Run all the wire through metal rods(X9) and screw two ends of metal rod into canopy and acrylic shade rings respectively, lock them tight with nuts. #③④
- Twist same color wires together and connect them to connector bar according to wire colors. Lift fixture to mounting plate and make electrical connections. Take the ground wire(green) off from transformer; connect one end to ground wire from outlet box and hook the other end(with metal ring end) to a nut nearby. Connect hot and neutral wires coming out from transformer (brown/blue) to hot and neutral wire from outlet box. #⑤⑥
- Carefully push wire connections back into outlet box. Slide canopy over mounting plate and lock canopy tight with ball nuts. #⑦⑧
- Reconnect electrical supply at fuse box/circuit breaker and test fixture.